

WHEELS

| | |
|-----------------------------------|-----------------|
| Product group | Wheels |
| Item number | 59915033 |
| Valid wheel size | 400 / 60 - 22.5 |
| Brand | BKT |
| Tread pattern | Flotation 648 |
| Valid rim size | 11.75 x 22.5 |
| Rim connection | 8/221/275 |
| Bolt hole design | A2 |
| Rim colour | Silver |
| Load capacity complete wheel [kg] | 4500 |
| Speed complete wheel [km/h] | 40 |
| Nettogewicht [kg] (gültig) | 100,84 |
| RDRA (Reifendruckregelanlage) | No |
| RDKS (Reifendruckkontrollsystem) | No |



Technical Informations

| | |
|-----------------------------|------------------------|
| Assembly Item no. Tyres | • 15712505 |
| LI / SI / PR | 148 A8 / 160 A8, 18 PR |
| Load capacity 1 [kg] | 3150 |
| Speed 1 [km/h]. | 40 |
| Load capacity 2 [kg] | 4500 |
| Speed 2 [km/h]. | 40 |
| Maximum air pressure [bar]. | 4,30 |
| TL/TT | TL |
| Tyre colour | Black |

| | |
|--------------------------------|-------------------------------|
| E-Ready | No |
| Antistatic | No |
| ECE regulation number | ECE 106 |
| Section width (mm) | 400 |
| Stat. radius (SLR) [mm] | 475 |
| Rolling circumference [mm]. | 3233 |
| Tread depth (mm) | 22,0 |
| Number of lugs | 27x2 |
| Assembly Item no. Rim | • 31612560 |
| Load capacity of rim 1 [kg] | 5400 |
| Speed Rims 1 [km/h] | 40 |
| Load capacity of rim 2 [kg] | 4500 |
| Speed Rims 2 [km/h] | 80 |
| Maximum speed [km/h]. | 40 |
| Type of drive | Angetriebene & gezogene Achse |
| Number of bolt holes | 8 |
| hub hole diameter [mm]. | 221 |
| Bolt hole circle diameter [mm] | 275 |
| Bolt hole diameter [mm] | 21.5 |
| Bolt hole design EUWA | B18 ES 32 |
| Countersinking | Sphere |
| Spherical countersink [mm]. | R16 |
| Rim centering | BC |
| Rim material | steel |
| RAL | RAL9006 |
| Valve seat | External Valve |
| Ventilation holes | No |

| | |
|--------------------------|-------------|
| Single / multi-part | einteilig |
| Hump | kein Hump |
| Cavity Sealed | No |
| Verschweißung beidseitig | No |
| Assembly Item no. Valve | • 47201038 |
| Preassembled valve | No |
| TPMS-kompatibles Ventil | No |
| Valve hole diameter [mm] | 15.7 |
| Valve design | Metal valve |
| Valve designation ETRTO | V5.01.1 |
| Valve length [mm] | 50.0 |
| Valve angle [°] | gerade |