

WHEELS

Product group	Wheels
Item number	59915035
Valid wheel size	400 / 60 - 22.5
Brand	BKT
Tread pattern	Flotation 648
Valid rim size	AG 11.75 x 22.5 H
Rim connection	8/221/275
Bolt hole design	B3
Offset (mm)	-50
Rim colour	Silver
Load capacity complete wheel [kg]	4500
Speed complete wheel [km/h]	40
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



Technical Informations

Assembly Item no. Tyres	• 15712505
LI / SI / PR	148 A8 / 160 A8, 18 PR
Load capacity 1 [kg]	3150
Speed 1 [km/h].	40
Load capacity 2 [kg]	4500
Speed 2 [km/h].	40
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	105,22

ECE regulation number	ECE 106
Section width (mm)	400
Stat. radius (SLR) [mm]	475
Rolling circumference [mm].	3233
Tread depth (mm)	22,0
Number of lugs	27x2
E-Ready	No
Assembly Item no. Rim	• 30840210
Load capacity of rim 1 [kg]	5450
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	4500
Speed Rims 2 [km/h]	80
Maximum speed [km/h].	40
Maximum air pressure [bar].	4,30
Number of bolt holes	8
Bolt hole design EUWA	B22 DS 36
hub hole diameter [mm].	221
Bolt hole circle diameter [mm]	275
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
Type of drive	Angetriebene & gezogene Achse
Hump	H
Single / multi-part	einteilig
Rim centering	BC
Rim material	steel
RAL	RAL9006

Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Valve seat	External Valve
Valve hole diameter [mm]	9.7
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve design	Metal valve
Valve designation ETRTO	V3.20.1
Valve length [mm]	41.0
Valve angle [°]	gerade