

## WHEELS

Product group	Wheels
Item number	59915157
Valid wheel size	710 / 45 R 22.5
Brand	BKT
Tread pattern	Ridemax FL 693 M
Valid rim size	AG 24.00 x 22.5 TH2
Rim connection	10/281/335
Bolt hole design	A3
Offset (mm)	-50
Rim colour	Silver
Rim series	Profiline
Load capacity complete wheel [kg]	5150
Speed complete wheel [km/h]	65
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



## Technical Informations

Assembly Item no. Tyres	• 15715169
LI / SI / PR	165 D
Load capacity 1 [kg]	5150
Speed 1 [km/h].	65
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	210,57

ECE regulation number	ECE 106
Section width (mm)	706
Stat. radius (SLR) [mm]	542
Rolling circumference [mm].	3658
Tread depth (mm)	22,0
E-Ready	No
Assembly Item no. Rim	• 32012784
Load capacity of rim 1 [kg]	8040
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	6640
Speed Rims 2 [km/h]	65
Maximum speed [km/h].	65
Maximum air pressure [bar].	4,00
Number of bolt holes	10
Bolt hole design EUWA	B22 ES 36
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
Type of drive	Angetriebene & gezogene Achse
Hump	TH2
Single / multi-part	einteilig
Rim centering	BC
Rim material	steel
RAL	RAL9006
Cavity Sealed	No

---

<b>Knurling</b>	without knurling
<b>Ventilation holes</b>	No
<b>Verschweißung beidseitig</b>	No
<b>Valve seat</b>	External Valve
<b>Valve hole diameter [mm]</b>	15.7
<b>Preassembled valve</b>	No
<b>TPMS-kompatibles Ventil</b>	No
<b>Valve design</b>	Rubber valve
<b>Valve length [mm]</b>	55.0
<b>Valve angle [°]</b>	gerade