

WHEELS

Product group	Wheels
Item number	59915180
Valid wheel size	28L R 26
Brand	BKT
Tread pattern	Ridemax FL 690
Valid rim size	DW 25 B x 26
Rim connection	10/281/335
Bolt hole design	A3
Rim colour	Silver
Load capacity complete wheel [kg]	7100
Speed complete wheel [km/h]	40



Technical Informations

Assembly Item no. Tyres	• 15715180
LI / SI / PR	176 A8 / 173 B
Load capacity 1 [kg]	7100
Speed 1 [km/h].	40
Load capacity 2 [kg]	6500
Speed 2 [km/h].	50
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	333,52
ECE regulation number	ECE 106

Section width (mm)	719
Stat. radius (SLR) [mm]	695
Rolling circumference [mm].	4745
Tread depth (mm)	30,0
E-Ready	No
Assembly Item no. Rim	• 32010433
Load capacity of rim 1 [kg]	9660
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	7300
Speed Rims 2 [km/h]	65
Maximum speed [km/h].	50
Maximum air pressure [bar].	2,80
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Knurling	without knurling
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	10
Bolt hole design EUWA	B22 ES 36
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18

hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade