

## WHEELS

Product group	Wheels
Item number	59915181
Valid wheel size	28L R 26
Brand	BKT
Tread pattern	Ridemax FL 690
Valid rim size	DW 25 B x 26
Rim connection	10/281/335
Bolt hole design	B3
Offset (mm)	-50
Rim colour	Silver
Load capacity complete wheel [kg]	7100
Speed complete wheel [km/h]	40



## Technical Informations

Assembly Item no. Tyres	• 15715180
LI / SI / PR	176 A8 / 173 B
Load capacity 1 [kg]	7100
Speed 1 [km/h].	40
Load capacity 2 [kg]	6500
Speed 2 [km/h].	50
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	334,52
ECE regulation number	ECE 106

Section width (mm)	719
Stat. radius (SLR) [mm]	695
Rolling circumference [mm].	4745
Tread depth (mm)	30,0
E-Ready	No
Assembly Item no. Rim	• 32010436
Load capacity of rim 1 [kg]	9660
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	7100
Speed Rims 2 [km/h]	65
Maximum speed [km/h].	50
Maximum air pressure [bar].	2,80
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Number of drain holes	6
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	10
Bolt hole design EUWA	B22 DS 36
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18

---

hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade