

WHEELS

Product group	Wheels
Item number	59915256
Valid wheel size	550 / 60 - 22.5
Brand	Alliance
Tread pattern	Flotation 328
Valid rim size	AG 16.00 x 22.5 TH2
Rim connection	8/221/275
Bolt hole design	B3
Offset (mm)	+70
Rim colour	Red
Load capacity complete wheel [kg]	5300
Speed complete wheel [km/h]	40



Technical Informations

Assembly Item no. Tyres	• 15212616
LI / SI / PR	154 A8 / 166 A8, 16 PR
Load capacity 1 [kg]	3750
Speed 1 [km/h].	40
Load capacity 2 [kg]	5300
Speed 2 [km/h].	40
Direction	Left
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	141,85
ECE regulation number	ECE 106

Section width (mm)	550
Stat. radius (SLR) [mm]	540
Speed Radius Index (SRI)	600
Rolling circumference [mm].	3765
E-Ready	No
Assembly Item no. Rim	• 30812686
Load capacity of rim 1 [kg]	5450
Speed Rims 1 [km/h]	40
Maximum speed [km/h].	40
Maximum air pressure [bar].	3,00
Type of drive	Angetriebene & gezogene Achse
Hump	TH2
Single / multi-part	einteilig
Rim material	steel
RAL	RAL3000
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	8
Bolt hole design EUWA	B22 DS 36
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
hub hole diameter [mm].	221
Bolt hole circle diameter [mm]	275
Valve seat	External Valve

Valve hole diameter [mm]	15.7
Preassembled valve	No
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade