

WHEELS

| | |
|-----------------------------------|--------------------|
| Product group | Wheels |
| Item number | 59915280 |
| Valid wheel size | 550 / 60 - 22.5 |
| Brand | Alliance |
| Tread pattern | Flotation 328 |
| Valid rim size | AG 16.00 x 22.5 H2 |
| Rim connection | 8/221/275 |
| Bolt hole design | A3 |
| Rim colour | Silver |
| Rim series | Profiline |
| Load capacity complete wheel [kg] | 4500 |
| Speed complete wheel [km/h] | 65 |



Technical Informations

| | |
|----------------------------|----------------------|
| Assembly Item no. Tyres | • 15212618 |
| LI / SI / PR | 160 D / 159 E, 16 PR |
| Load capacity 1 [kg] | 4500 |
| Speed 1 [km/h]. | 65 |
| Load capacity 2 [kg] | 4375 |
| Speed 2 [km/h]. | 70 |
| Carcass properties | High Speed |
| Antistatic | No |
| Tyre colour | Black |
| Nettogewicht [kg] (gültig) | 141,73 |
| ECE regulation number | ECE 106 |

| | |
|-----------------------------|-------------------------------|
| Section width (mm) | 550 |
| Stat. radius (SLR) [mm] | 540 |
| Speed Radius Index (SRI) | 575 |
| Rolling circumference [mm]. | 3580 |
| Tread depth (mm) | 25,0 |
| E-Ready | No |
| Assembly Item no. Rim | • 31612603 |
| Load capacity of rim 1 [kg] | 6700 |
| Speed Rims 1 [km/h] | 40 |
| Load capacity of rim 2 [kg] | 4800 |
| Speed Rims 2 [km/h] | 65 |
| Maximum speed [km/h]. | 70 |
| Maximum air pressure [bar]. | 2,80 |
| Type of drive | Angetriebene & gezogene Achse |
| Hump | H2 |
| Valve protection | VS H |
| Single / multi-part | einteilig |
| Rim material | steel |
| RAL | RAL9006 |
| Cavity Sealed | No |
| Number of additional holes | 8 |
| Ventilation holes | No |
| Verschweißung beidseitig | No |
| Rim centering | BC |
| Number of bolt holes | 8 |
| Bolt hole design EUWA | B22 ES 36 |
| Bolt hole diameter [mm] | 27 |

| | |
|--------------------------------|----------------|
| Countersinking | Sphere |
| Spherical countersink [mm]. | R18 |
| hub hole diameter [mm]. | 221 |
| Bolt hole circle diameter [mm] | 275 |
| Valve seat | External Valve |
| Valve hole diameter [mm] | 15.7 |
| Preassembled valve | No |
| Valve design | Metal valve |
| Valve designation ETRTO | V5.01.1 |
| Valve length [mm] | 50.0 |
| Valve angle [°] | gerade |