

## WHEELS

Product group	Wheels
Item number	59915299
Valid wheel size	400 / 55 - 22.5
Brand	BKT
Tread pattern	AW 705
Valid rim size	11.75 x 22.5
Rim connection	8/221/275
Bolt hole design	A2
Rim colour	Silver
Load capacity complete wheel [kg]	3750
Speed complete wheel [km/h]	40
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



## Technical Informations

Assembly Item no. Tyres	• 15712488
LI / SI / PR	154 A8, 18 PR
Load capacity 1 [kg]	3750
Speed 1 [km/h].	40
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	93,19
ECE regulation number	ECE 106
Section width (mm)	405
Stat. radius (SLR) [mm]	443

Rolling circumference [mm].	3072
Tread depth (mm)	13,0
E-Ready	No
Assembly Item no. Rim	• 31612560
Load capacity of rim 1 [kg]	5400
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	4500
Speed Rims 2 [km/h]	80
Maximum speed [km/h].	40
Maximum air pressure [bar].	4,50
Number of bolt holes	8
hub hole diameter [mm].	221
Bolt hole circle diameter [mm]	275
Bolt hole diameter [mm]	21.5
Countersinking	Sphere
Spherical countersink [mm].	R16
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Single / multi-part	einteilig
Rim centering	BC
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Valve seat	External Valve
Valve hole diameter [mm]	15.7

---

Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve design	Metal valve
Valve designation ETRTO	V3.20.1
Valve length [mm]	41.0
Valve angle [°]	gerade