

WHEELS

Product group	Wheels
Item number	59915514
Valid wheel size	620 / 40 R 22.5
Brand	Alliance
Tread pattern	380
Valid rim size	AG 20.00 x 22.5 H2
Rim connection	10/281/335
Bolt hole design	A3
Offset (mm)	-50
Rim colour	Silver
Load capacity complete wheel [kg]	3875
Speed complete wheel [km/h]	65



Technical Informations

Assembly Item no. Tyres	• 15215642
LI / SI / PR	155 D
Load capacity 1 [kg]	3875
Speed 1 [km/h].	65
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	166,52
ECE regulation number	ECE 106
Section width (mm)	620
Stat. radius (SLR) [mm]	488

Rolling circumference [mm].	3352
Tread depth (mm)	26,0
E-Ready	No
Assembly Item no. Rim	• 33060407
Load capacity of rim 1 [kg]	7600
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	5600
Speed Rims 2 [km/h]	65
Maximum speed [km/h].	65
Maximum air pressure [bar].	4,00
Type of drive	Angetriebene & gezogene Achse
Hump	H2
Valve protection	VS H
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	10
Bolt hole design EUWA	B22 ES 36
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335

Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade