

## WHEELS

|                                   |                    |
|-----------------------------------|--------------------|
| Product group                     | Wheels             |
| Item number                       | 59915528           |
| Valid wheel size                  | 620 / 40 R 22.5    |
| Brand                             | Alliance           |
| Tread pattern                     | Flotmaster 381     |
| Valid rim size                    | AG 20.00 x 22.5 H2 |
| Rim connection                    | 8/221/275          |
| Bolt hole design                  | A2                 |
| Rim colour                        | Silver             |
| Load capacity complete wheel [kg] | 3750               |
| Speed complete wheel [km/h]       | 65                 |



## Technical Informations

|                            |              |
|----------------------------|--------------|
| Assembly Item no. Tyres    | • 15216125   |
| LI / SI / PR               | 154 D        |
| Load capacity 1 [kg]       | 3750         |
| Speed 1 [km/h].            | 65           |
| Carcass properties         | Steel Belted |
| Antistatic                 | No           |
| Tyre colour                | Black        |
| Nettogewicht [kg] (gültig) | 165,21       |
| ECE regulation number      | ECE 106      |
| Section width (mm)         | 612          |
| Stat. radius (SLR) [mm]    | 486          |

|                                |                               |
|--------------------------------|-------------------------------|
| Rolling circumference [mm].    | 3278                          |
| Tread depth (mm)               | 18,0                          |
| Tyre capacity 75% [litr.]      | 281                           |
| E-Ready                        | No                            |
| Assembly Item no. Rim          | • 33060406                    |
| Load capacity of rim 1 [kg]    | 7600                          |
| Speed Rims 1 [km/h]            | 40                            |
| Load capacity of rim 2 [kg]    | 5600                          |
| Speed Rims 2 [km/h]            | 65                            |
| Maximum speed [km/h].          | 65                            |
| Maximum air pressure [bar].    | 4,00                          |
| Type of drive                  | Angetriebene & gezogene Achse |
| Hump                           | H2                            |
| Single / multi-part            | einteilig                     |
| Rim material                   | steel                         |
| RAL                            | RAL9006                       |
| Cavity Sealed                  | No                            |
| Ventilation holes              | No                            |
| Verschweißung beidseitig       | No                            |
| Rim centering                  | BC                            |
| Number of bolt holes           | 8                             |
| Bolt hole diameter [mm]        | 21.5                          |
| Countersinking                 | Sphere                        |
| Spherical countersink [mm].    | R16                           |
| hub hole diameter [mm].        | 221                           |
| Bolt hole circle diameter [mm] | 275                           |
| Valve seat                     | External Valve                |

---

|                          |             |
|--------------------------|-------------|
| Valve hole diameter [mm] | 15.7        |
| Preassembled valve       | No          |
| Valve design             | Metal valve |
| Valve designation ETRTO  | V5.01.1     |
| Valve length [mm]        | 50.0        |
| Valve angle [°]          | gerade      |