

## WHEELS

Product group	Wheels
Item number	59915551
Valid wheel size	700 / 50 - 22.5
Brand	Alliance
Tread pattern	Flotation 331
Valid rim size	AG 24.00 x 22.5 TH2
Rim connection	8/221/275
Bolt hole design	A3
Rim colour	Red
Rim series	Profiline
Load capacity complete wheel [kg]	6700
Speed complete wheel [km/h]	40



## Technical Informations

Assembly Item no. Tyres	• 15212655
LI / SI / PR	162 A8 / 174 A8, 16 PR
Load capacity 1 [kg]	4750
Speed 1 [km/h].	40
Load capacity 2 [kg]	6700
Speed 2 [km/h].	40
Direction	Left
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	217,57
ECE regulation number	ECE 106

Section width (mm)	700
Stat. radius (SLR) [mm]	550
Rolling circumference [mm].	3650
Tread depth (mm)	39,0
E-Ready	No
Assembly Item no. Rim	• 32012786
Load capacity of rim 1 [kg]	8040
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	6640
Speed Rims 2 [km/h]	65
Maximum speed [km/h].	50
Maximum air pressure [bar].	2,40
Type of drive	Angetriebene & gezogene Achse
Hump	TH2
Single / multi-part	einteilig
Rim material	steel
RAL	RAL3000
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	8
Bolt hole design EUWA	B22 ES 36
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
hub hole diameter [mm].	221

---

<b>Bolt hole circle diameter [mm]</b>	275
<b>Valve seat</b>	External Valve
<b>Valve hole diameter [mm]</b>	15.7
<b>Preassembled valve</b>	No
<b>Valve design</b>	Rubber valve
<b>Valve length [mm]</b>	55.0
<b>Valve angle [°]</b>	gerade