

WHEELS

Product group	Wheels
Item number	59915583
Valid wheel size	700 / 50 - 22.5
Brand	Alliance
Tread pattern	Flotation 328
Valid rim size	AG 24.00 x 22.5 TH2
Rim connection	10/281/335
Bolt hole design	A3
Offset (mm)	-100
Rim colour	Silver
Rim series	Profiline
Load capacity complete wheel [kg]	5300
Speed complete wheel [km/h]	65



Technical Informations

Assembly Item no. Tyres	• 15212670
LI / SI / PR	167 D / 166 E, 16 PR
Load capacity 1 [kg]	5450
Speed 1 [km/h].	65
Load capacity 2 [kg]	5300
Speed 2 [km/h].	70
Carcass properties	High Speed
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	198,32

ECE regulation number	ECE 106
Section width (mm)	700
Stat. radius (SLR) [mm]	550
Speed Radius Index (SRI)	600
Rolling circumference [mm].	3650
Tread depth (mm)	25,0
E-Ready	No
Assembly Item no. Rim	• 32012785
Load capacity of rim 1 [kg]	8040
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	6640
Speed Rims 2 [km/h]	65
Maximum speed [km/h].	65
Maximum air pressure [bar].	2,80
Type of drive	Angetriebene & gezogene Achse
Hump	TH2
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Knurling	without knurling
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	10
Bolt hole design EUWA	B22 ES 36
Bolt hole diameter [mm]	27

Countersinking	Sphere
Spherical countersink [mm].	R18
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
Valve design	Rubber valve
Valve length [mm]	55.0
Valve angle [°]	gerade