

WHEELS

Product group	Wheels
Item number	59915618
Valid wheel size	560 / 60 R 22.5
Brand	Alliance
Tread pattern	380 Industrial HD
Valid rim size	AG 16.00 x 22.5 TH2
Rim connection	10/281/335
Bolt hole design	A3
Offset (mm)	-50
Rim colour	Silver
Load capacity complete wheel [kg]	5300
Speed complete wheel [km/h]	40



Technical Informations

Assembly Item no. Tyres	• 15215534
LI / SI / PR	172 D
Load capacity 1 [kg]	6300
Speed 1 [km/h].	65
Carcass properties	Steel Belted HD
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	167,79
ECE regulation number	ECE 106
Section width (mm)	550
Stat. radius (SLR) [mm]	553

Rolling circumference [mm].	3849
Tread depth (mm)	23,0
Number of lugs	18x2
Tyre capacity 75% [ltr.]	276.75
E-Ready	No
Assembly Item no. Rim	• 30812681
Load capacity of rim 1 [kg]	7250
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	5300
Speed Rims 2 [km/h]	65
Maximum speed [km/h].	65
Maximum air pressure [bar].	5,00
Type of drive	Angetriebene & gezogene Achse
Hump	TH2
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	10
Bolt hole design EUWA	B22 ES 36
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
hub hole diameter [mm].	281

Bolt hole circle diameter [mm]	335
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade