

WHEELS

Product group	Wheels
Item number	59915631
Valid wheel size	650 / 50 R 22.5
Brand	Alliance
Tread pattern	885
Valid rim size	AG 20.00 x 22.5 TH2
Rim connection	8/221/275
Bolt hole design	A2
Offset (mm)	-50
Rim colour	Silver
Rim series	Profiline
Load capacity complete wheel [kg]	4875
Speed complete wheel [km/h]	65



Technical Informations

Assembly Item no. Tyres	• 15216249
LI / SI / PR	163 D
Load capacity 1 [kg]	4875
Speed 1 [km/h].	65
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	193,17
ECE regulation number	ECE 106
Section width (mm)	650

Stat. radius (SLR) [mm]	554
Speed Radius Index (SRI)	575
Rolling circumference [mm].	3630
Tread depth (mm)	20,0
Number of lugs	27x2
E-Ready	No
Assembly Item no. Rim	• 32012682
Load capacity of rim 1 [kg]	7070
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	5310
Speed Rims 2 [km/h]	65
Maximum speed [km/h].	65
Maximum air pressure [bar].	4,00
Type of drive	Angetriebene & gezogene Achse
Hump	TH2
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	8
Bolt hole diameter [mm]	21.5
Countersinking	Sphere
Spherical countersink [mm].	R16
hub hole diameter [mm].	221

Bolt hole circle diameter [mm]	275
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade