

WHEELS

Product group	Wheels
Item number	59915703
Valid wheel size	600 / 55 - 26.5
Brand	Alliance
Tread pattern	Flotation 331
Valid rim size	AG 20.00 x 26.5 TH2
Rim connection	10/281/335
Bolt hole design	A3
Offset (mm)	-100
Rim series	Profiline
Load capacity complete wheel [kg]	6000
Speed complete wheel [km/h]	40



Technical Informations

Assembly Item no. Tyres	• 15212740
LI / SI / PR	159 A8 / 170 A8, 16 PR
Load capacity 1 [kg]	4375
Speed 1 [km/h].	40
Load capacity 2 [kg]	6000
Speed 2 [km/h].	40
Direction	Right
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	216,77
ECE regulation number	ECE 106

Section width (mm)	591
Stat. radius (SLR) [mm]	580
Rolling circumference [mm].	3850
Tread depth (mm)	40,0
E-Ready	No
Assembly Item no. Rim	• 32012868
Load capacity of rim 1 [kg]	10200
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	7300
Speed Rims 2 [km/h]	70
Maximum speed [km/h].	40
Maximum air pressure [bar].	2,60
Type of drive	Angetriebene & gezogene Achse
Hump	TH2
Single / multi-part	einteilig
Rim material	steel
Rim colour (manufacturer's designation)	Fendt Terra - red
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	10
Bolt hole design EUWA	B22 ES 36
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
hub hole diameter [mm].	281

Bolt hole circle diameter [mm]	335
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade