

WHEELS

Product group	Wheels
Item number	59915705
Valid wheel size	600 / 55 - 26.5
Brand	Alliance
Tread pattern	Flotation 331
Valid rim size	AG 20.00 x 26.5 TH2
Rim connection	10/281/335
Bolt hole design	A3
Offset (mm)	-100
Rim series	Profiline
Load capacity complete wheel [kg]	6000
Speed complete wheel [km/h]	40



Technical Informations

Assembly Item no. Tyres	• 15212740
LI / SI / PR	159 A8 / 170 A8, 16 PR
Load capacity 1 [kg]	4375
Speed 1 [km/h].	40
Load capacity 2 [kg]	6000
Speed 2 [km/h].	40
Direction	Right
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	216,77
ECE regulation number	ECE 106

Section width (mm)	591
Stat. radius (SLR) [mm]	580
Rolling circumference [mm].	3850
Tread depth (mm)	40,0
E-Ready	No
Assembly Item no. Rim	• 32012869
Load capacity of rim 1 [kg]	10200
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	7300
Speed Rims 2 [km/h]	70
Maximum speed [km/h].	40
Maximum air pressure [bar].	2,60
Type of drive	Angetriebene & gezogene Achse
Hump	TH2
Single / multi-part	einteilig
Rim material	steel
Rim colour (manufacturer's designation)	Sapphire grey
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	10
Bolt hole design EUWA	B22 ES 36
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
hub hole diameter [mm].	281

Bolt hole circle diameter [mm]	335
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade