

## WHEELS

Product group	Wheels
Item number	59915716
Valid wheel size	650 / 65 R 26.5
Brand	Alliance
Tread pattern	388
Valid rim size	AG 20.00 x 26.5 H2
Rim connection	12/371/425
Bolt hole design	A3
Offset (mm)	-40
Rim colour	Anthrazit
Load capacity complete wheel [kg]	5150
Speed complete wheel [km/h]	65



## Technical Informations

Assembly Item no. Tyres	• 15215743
LI / SI / PR	165 D
Load capacity 1 [kg]	5150
Speed 1 [km/h].	65
Carcass properties	Steel Belted
Direction	Left
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	246,18
ECE regulation number	ECE 106
Section width (mm)	651

Stat. radius (SLR) [mm]	661
Rolling circumference [mm].	4509
Tread depth (mm)	25,0
E-Ready	No
Assembly Item no. Rim	• 33060558
Load capacity of rim 1 [kg]	10200
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	7500
Speed Rims 2 [km/h]	65
Maximum speed [km/h].	65
Maximum air pressure [bar].	2,80
Type of drive	Angetriebene & gezogene Achse
Hump	H2
Valve protection	VS H
Single / multi-part	einteilig
Rim material	steel
RAL	RAL7016
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	12
Bolt hole design EUWA	B22 ES 36
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
hub hole diameter [mm].	371

---

<b>Bolt hole circle diameter [mm]</b>	425
<b>Valve seat</b>	External Valve
<b>Valve hole diameter [mm]</b>	15.7
<b>Preassembled valve</b>	No
<b>Valve design</b>	Metal valve
<b>Valve designation ETRTO</b>	V5.01.1
<b>Valve length [mm]</b>	50.0
<b>Valve angle [°]</b>	gerade