

## WHEELS

Product group	Wheels
Item number	59915756
Valid wheel size	VF 600 / 55 R 26.5
Brand	Alliance
Tread pattern	Agriflex 389 +
Valid rim size	AG 20.00 x 26.5 TH2
Rim connection	8/221/275
Bolt hole design	A2
Rim colour	Silver
Rim series	Profiline
Load capacity complete wheel [kg]	5450
Speed complete wheel [km/h]	65



## Technical Informations

Assembly Item no. Tyres	• 15215695
LI / SI / PR	167 D
Load capacity 1 [kg]	5450
Speed 1 [km/h].	65
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	241,01
ECE regulation number	ECE 106
Section width (mm)	629
Stat. radius (SLR) [mm]	586

Rolling circumference [mm].	4065
Tread depth (mm)	26,0
Number of lugs	21x2
Tyre capacity 75% [ltr.]	354.75
E-Ready	No
Assembly Item no. Rim	• 32012880
Load capacity of rim 1 [kg]	8840
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	6500
Speed Rims 2 [km/h]	65
Maximum speed [km/h].	65
Maximum air pressure [bar].	2,80
Type of drive	Angetriebene & gezogene Achse
Hump	TH2
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Knurling	without knurling
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	8
Bolt hole diameter [mm]	21.5
Countersinking	Sphere
Spherical countersink [mm].	R16
hub hole diameter [mm].	221

---

<b>Bolt hole circle diameter [mm]</b>	275
<b>Valve seat</b>	External Valve
<b>Valve hole diameter [mm]</b>	15.7
<b>Preassembled valve</b>	No
<b>Valve design</b>	Rubber valve
<b>Valve length [mm]</b>	55.0
<b>Valve angle [°]</b>	gerade