

WHEELS

Product group	Wheels
Item number	59915862
Valid wheel size	VF 750 / 45 R 26.5
Brand	Alliance
Tread pattern	Agriflex 389 +
Valid rim size	AG 24.00 x 26.5 TH2
Rim connection	8/221/275
Bolt hole design	A2
Rim colour	Silver
Rim series	Profiline
Load capacity complete wheel [kg]	6300
Speed complete wheel [km/h]	65



Technical Informations

Assembly Item no. Tyres	• 15215756
LI / SI / PR	172 D
Load capacity 1 [kg]	6300
Speed 1 [km/h].	65
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	263,01
ECE regulation number	ECE 106
Section width (mm)	754
Stat. radius (SLR) [mm]	589

Rolling circumference [mm].	4086
Tread depth (mm)	26,0
Number of lugs	21x2
Tyre capacity 75% [ltr.]	459.75
E-Ready	No
Assembly Item no. Rim	• 32012900
Load capacity of rim 1 [kg]	8570
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	6300
Speed Rims 2 [km/h]	65
Maximum speed [km/h].	65
Maximum air pressure [bar].	2,80
Type of drive	Angetriebene & gezogene Achse
Hump	TH2
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	8
Bolt hole diameter [mm]	21.5
Countersinking	Sphere
Spherical countersink [mm].	R16
hub hole diameter [mm].	221
Bolt hole circle diameter [mm]	275

Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
Valve design	Rubber valve
Valve length [mm]	55.0
Valve angle [°]	gerade