

## WHEELS

|                                   |                     |
|-----------------------------------|---------------------|
| Product group                     | Wheels              |
| Item number                       | 59915873            |
| Valid wheel size                  | VF 750 / 45 R 26.5  |
| Brand                             | Alliance            |
| Tread pattern                     | Agriflex 389 +      |
| Valid rim size                    | AG 24.00 x 26.5 TH2 |
| Rim connection                    | 10/281/335          |
| Bolt hole design                  | A3                  |
| Rim colour                        | Silver              |
| Rim series                        | Profiline           |
| Load capacity complete wheel [kg] | 6300                |
| Speed complete wheel [km/h]       | 65                  |



## Technical Informations

|                            |              |
|----------------------------|--------------|
| Assembly Item no. Tyres    | • 15215756   |
| LI / SI / PR               | 172 D        |
| Load capacity 1 [kg]       | 6300         |
| Speed 1 [km/h].            | 65           |
| Carcass properties         | Steel Belted |
| Antistatic                 | No           |
| Tyre colour                | Black        |
| Nettogewicht [kg] (gültig) | 274,01       |
| ECE regulation number      | ECE 106      |
| Section width (mm)         | 754          |
| Stat. radius (SLR) [mm]    | 589          |

|                             |                               |
|-----------------------------|-------------------------------|
| Rolling circumference [mm]. | 4086                          |
| Tread depth (mm)            | 26,0                          |
| Number of lugs              | 21x2                          |
| Tyre capacity 75% [ltr.]    | 459.75                        |
| E-Ready                     | No                            |
| Assembly Item no. Rim       | • 32012902                    |
| Load capacity of rim 1 [kg] | 10200                         |
| Speed Rims 1 [km/h]         | 40                            |
| Load capacity of rim 2 [kg] | 7500                          |
| Speed Rims 2 [km/h]         | 65                            |
| Maximum speed [km/h].       | 65                            |
| Maximum air pressure [bar]. | 2,80                          |
| Type of drive               | Angetriebene & gezogene Achse |
| Hump                        | TH2                           |
| Single / multi-part         | einteilig                     |
| Rim material                | steel                         |
| RAL                         | RAL9006                       |
| Cavity Sealed               | No                            |
| Knurling                    | without knurling              |
| Ventilation holes           | No                            |
| Verschweißung beidseitig    | No                            |
| Rim centering               | BC                            |
| Number of bolt holes        | 10                            |
| Bolt hole design EUWA       | B22 ES 36                     |
| Bolt hole diameter [mm]     | 27                            |
| Countersinking              | Sphere                        |
| Spherical countersink [mm]. | R18                           |

---

|                                |                |
|--------------------------------|----------------|
| hub hole diameter [mm].        | 281            |
| Bolt hole circle diameter [mm] | 335            |
| Valve seat                     | External Valve |
| Valve hole diameter [mm]       | 15.7           |
| Preassembled valve             | No             |
| Valve design                   | Rubber valve   |
| Valve length [mm]              | 55.0           |
| Valve angle [°]                | gerade         |