

## WHEELS

Product group	Wheels
Item number	59915932
Valid wheel size	560 / 45 R 22.5
Brand	Alliance
Tread pattern	Flotmaster 381
Valid rim size	AG 16.00 x 22.5 H2
Rim connection	8/221/275
Bolt hole design	A2
Rim colour	Silver
Rim series	Profiline
Load capacity complete wheel [kg]	3000
Speed complete wheel [km/h]	65



## Technical Informations

Assembly Item no. Tyres	• 15216110
LI / SI / PR	146 D
Load capacity 1 [kg]	3000
Speed 1 [km/h].	65
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	134,88
ECE regulation number	ECE 106
Section width (mm)	540
Stat. radius (SLR) [mm]	485

Rolling circumference [mm].	3304
Tread depth (mm)	18,5
E-Ready	No
Assembly Item no. Rim	• 31612621
Load capacity of rim 1 [kg]	6700
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	4800
Speed Rims 2 [km/h]	65
Maximum speed [km/h].	65
Maximum air pressure [bar].	3,20
Type of drive	Angetriebene & gezogene Achse
Hump	H2
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Number of additional holes	8
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	8
Bolt hole diameter [mm]	21.5
Countersinking	Sphere
Spherical countersink [mm].	R16
hub hole diameter [mm].	221
Bolt hole circle diameter [mm]	275
Valve seat	External Valve

---

Valve hole diameter [mm]	15.7
Preassembled valve	No
Valve design	Rubber valve
Valve length [mm]	55.0
Valve angle [°]	gerade