

WHEELS

Product group	Wheels
Item number	59915940
Valid wheel size	700 / 50 - 26.5
Brand	Alliance
Tread pattern	Flotation 328
Valid rim size	AG 24.00 x 26.5 TH2
Rim connection	8/221/275
Bolt hole design	A2
Rim colour	Silver
Rim series	Profiline
Load capacity complete wheel [kg]	6000
Speed complete wheel [km/h]	50



Technical Informations

Assembly Item no. Tyres	• 15212831
LI / SI / PR	170 B / 166 C, 16 PR
Load capacity 1 [kg]	6000
Speed 1 [km/h].	50
Load capacity 2 [kg]	5300
Speed 2 [km/h].	60
Carcass properties	High Speed
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	222,97
ECE regulation number	ECE 106

Section width (mm)	700
Stat. radius (SLR) [mm]	580
Speed Radius Index (SRI)	650
Rolling circumference [mm].	3974
Tread depth (mm)	25,0
E-Ready	No
Assembly Item no. Rim	• 32012900
Load capacity of rim 1 [kg]	8570
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	6300
Speed Rims 2 [km/h]	65
Maximum speed [km/h].	60
Maximum air pressure [bar].	2,40
Number of bolt holes	8
hub hole diameter [mm].	221
Bolt hole circle diameter [mm]	275
Bolt hole diameter [mm]	21.5
Countersinking	Sphere
Spherical countersink [mm].	R16
Type of drive	Angetriebene & gezogene Achse
Hump	TH2
Single / multi-part	einteilig
Rim centering	BC
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No

Verschweißung beidseitig	No
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve design	Rubber valve
Valve length [mm]	55.0
Valve angle [°]	gerade