

## WHEELS

|                                   |                     |
|-----------------------------------|---------------------|
| Product group                     | Wheels              |
| Item number                       | 59915952            |
| Valid wheel size                  | 560 / 45 R 22.5     |
| Brand                             | Alliance            |
| Tread pattern                     | 380                 |
| Valid rim size                    | AG 16.00 x 22.5 TH2 |
| Rim connection                    | 10/281/335          |
| Bolt hole design                  | A3                  |
| Offset (mm)                       | -50                 |
| Rim colour                        | Silver              |
| Load capacity complete wheel [kg] | 3550                |
| Speed complete wheel [km/h]       | 65                  |



## Technical Informations

|                            |              |
|----------------------------|--------------|
| Assembly Item no. Tyres    | • 15215513   |
| LI / SI / PR               | 152 D        |
| Load capacity 1 [kg]       | 3550         |
| Speed 1 [km/h].            | 65           |
| Carcass properties         | Steel Belted |
| Antistatic                 | No           |
| Tyre colour                | Black        |
| Nettogewicht [kg] (gültig) | 138,52       |
| ECE regulation number      | ECE 106      |
| Section width (mm)         | 554          |
| Stat. radius (SLR) [mm]    | 484          |

|                             |                               |
|-----------------------------|-------------------------------|
| Speed Radius Index (SRI)    | 525                           |
| Rolling circumference [mm]. | 3263                          |
| Tread depth (mm)            | 25,0                          |
| Number of lugs              | 16x2                          |
| E-Ready                     | No                            |
| Assembly Item no. Rim       | • 30812681                    |
| Load capacity of rim 1 [kg] | 7250                          |
| Speed Rims 1 [km/h]         | 40                            |
| Load capacity of rim 2 [kg] | 5300                          |
| Speed Rims 2 [km/h]         | 65                            |
| Maximum speed [km/h].       | 65                            |
| Maximum air pressure [bar]. | 4,00                          |
| Type of drive               | Angetriebene & gezogene Achse |
| Hump                        | TH2                           |
| Single / multi-part         | einteilig                     |
| Rim material                | steel                         |
| RAL                         | RAL9006                       |
| Cavity Sealed               | No                            |
| Ventilation holes           | No                            |
| Verschweißung beidseitig    | No                            |
| Rim centering               | BC                            |
| Number of bolt holes        | 10                            |
| Bolt hole design EUWA       | B22 ES 36                     |
| Bolt hole diameter [mm]     | 27                            |
| Countersinking              | Sphere                        |
| Spherical countersink [mm]. | R18                           |
| hub hole diameter [mm].     | 281                           |

---

|                                       |                |
|---------------------------------------|----------------|
| <b>Bolt hole circle diameter [mm]</b> | 335            |
| <b>Valve seat</b>                     | External Valve |
| <b>Valve hole diameter [mm]</b>       | 15.7           |
| <b>Preassembled valve</b>             | No             |
| <b>Valve design</b>                   | Metal valve    |
| <b>Valve designation ETRTO</b>        | V5.01.1        |
| <b>Valve length [mm]</b>              | 50.0           |
| <b>Valve angle [°]</b>                | gerade         |