

WHEELS

Product group	Wheels
Item number	59916017
Valid wheel size	800 / 45 R 26.5
Brand	Alliance
Tread pattern	885
Valid rim size	AG 28.00 x 26.5 TH2
Rim connection	10/281/335
Bolt hole design	A3
Offset (mm)	-100
Rim colour	Silver
Rim series	Profiline
Load capacity complete wheel [kg]	6700
Speed complete wheel [km/h]	65



Technical Informations

Assembly Item no. Tyres	• 15216258
LI / SI / PR	174 D
Load capacity 1 [kg]	6700
Speed 1 [km/h].	65
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	303,45
ECE regulation number	ECE 106
Section width (mm)	800
Stat. radius (SLR) [mm]	623

Dynamic radius [mm]	651.5
Rolling circumference [mm].	4216
Tread depth (mm)	26,8
E-Ready	No
Assembly Item no. Rim	• 32013032
Load capacity of rim 1 [kg]	9930
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	7300
Speed Rims 2 [km/h]	65
Maximum speed [km/h].	65
Maximum air pressure [bar].	4,00
Type of drive	Angetriebene & gezogene Achse
Hump	TH2
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Knurling	without knurling
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	10
Bolt hole design EUWA	B22 ES 36
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
hub hole diameter [mm].	281

Bolt hole circle diameter [mm]	335
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade