

WHEELS

Product group	Wheels
Item number	59916234
Valid wheel size	650 / 65 R 38
Brand	Alliance
Tread pattern	360
Valid rim size	TW 20 B x 38
Rim connection	10/281/335
Bolt hole design	A3
Rim colour	Silver
Load capacity complete wheel [kg]	7500
Speed complete wheel [km/h]	40
Nettogewicht [kg] (gültig)	395,03
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



Technical Informations

Assembly Item no. Tyres	• 15226794
LI / SI / PR	178 A8 / 175 B
Load capacity 1 [kg]	7500
Speed 1 [km/h].	40
Load capacity 2 [kg]	6900
Speed 2 [km/h].	50
Maximum air pressure [bar].	3,50
TL/TT	TL
Tyre colour	Black

E-Ready	No
Antistatic	No
ECE regulation number	ECE 106
Section width (mm)	645
Stat. radius (SLR) [mm]	830
Rolling circumference [mm].	5500
Tread depth (mm)	50,5
Number of lugs	23x2
Tyre capacity 75% [ltr.]	559
Assembly Item no. Rim	• 32013645
Load capacity of rim 1 [kg]	7500
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	7000
Speed Rims 2 [km/h]	50
Maximum speed [km/h].	50
Type of drive	Towed axle
Number of bolt holes	10
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Bolt hole diameter [mm]	27
Bolt hole design EUWA	B22 ES 36
Countersinking	Sphere
Spherical countersink [mm].	R18
Rim centering	BC
Rim material	steel
RAL	RAL9006
Valve seat	External Valve

Ventilation holes	No
Single / multi-part	einteilig
Hump	kein Hump
Cavity Sealed	No
Knurling	without knurling
Verschweißung beidseitig	No
Assembly Item no. Valve	• 47201038
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve hole diameter [mm]	15.7
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade