

## WHEELS

Product group	Wheels
Item number	59916235
Valid wheel size	650 / 65 R 38
Brand	Alliance
Tread pattern	360
Valid rim size	TW 20 B x 38
Rim connection	10/281/335
Bolt hole design	A3
Offset (mm)	-50
Rim colour	Silver
Load capacity complete wheel [kg]	7500
Speed complete wheel [km/h]	40



## Technical Informations

Assembly Item no. Tyres	• 15226794
LI / SI / PR	178 A8 / 175 B
Load capacity 1 [kg]	7500
Speed 1 [km/h].	40
Load capacity 2 [kg]	6900
Speed 2 [km/h].	50
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	395,03
ECE regulation number	ECE 106
Section width (mm)	645

Stat. radius (SLR) [mm]	830
Rolling circumference [mm].	5500
Tread depth (mm)	50,5
Number of lugs	23x2
Tyre capacity 75% [ltr.]	559
E-Ready	No
Assembly Item no. Rim	• 32013643
Load capacity of rim 1 [kg]	7500
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	7000
Speed Rims 2 [km/h]	50
Maximum speed [km/h].	40
Maximum air pressure [bar].	3,50
Type of drive	Towed axle
Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Knurling	without knurling
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	10
Bolt hole design EUWA	B22 ES 36
Bolt hole diameter [mm]	27
Countersinking	Sphere

---

Spherical countersink [mm].	R18
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade