

## WHEELS

Product group	Wheels
Item number	59916236
Valid wheel size	580 / 70 R 38
Brand	Alliance
Tread pattern	370
Valid rim size	DW 18 L x 38
Rim connection	10/281/335
Bolt hole design	A3
Rim colour	Silver
Load capacity complete wheel [kg]	8000
Speed complete wheel [km/h]	40



## Technical Informations

Assembly Item no. Tyres	• 15225237
LI / SI / PR	180 A8
Load capacity 1 [kg]	8000
Speed 1 [km/h].	40
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	369,64
ECE regulation number	ECE 106
Section width (mm)	577
Stat. radius (SLR) [mm]	816
Rolling circumference [mm].	5343

Tread depth (mm)	58,0
Number of lugs	18x2
Tyre capacity 75% [litr.]	547.5
E-Ready	No
Assembly Item no. Rim	• 39122972
Load capacity of rim 1 [kg]	8000
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	7040
Speed Rims 2 [km/h]	65
Maximum speed [km/h].	40
Maximum air pressure [bar].	4,60
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	10
Bolt hole design EUWA	B22 ES 36
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335

---

Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade