

WHEELS

| | |
|-----------------------------------|--------------|
| Product group | Wheels |
| Item number | 59916243 |
| Valid wheel size | 20.8 - 38 |
| Brand | Alliance |
| Tread pattern | 347 |
| Valid rim size | DW 18 L x 38 |
| Rim connection | 10/281/335 |
| Bolt hole design | A3 |
| Rim colour | Silver |
| Load capacity complete wheel [kg] | 4375 |
| Speed complete wheel [km/h] | 40 |



Technical Informations

| | |
|-----------------------------|---------------|
| Assembly Item no. Tyres | • 15222840 |
| LI / SI / PR | 159 A8, 14 PR |
| Load capacity 1 [kg] | 4375 |
| Speed 1 [km/h]. | 40 |
| Antistatic | No |
| Tyre colour | Black |
| Nettogewicht [kg] (gültig) | 318,26 |
| ECE regulation number | ECE 106 |
| Section width (mm) | 528 |
| Stat. radius (SLR) [mm] | 826 |
| Rolling circumference [mm]. | 5411 |

| | |
|--------------------------------|-------------------------------|
| Tread depth (mm) | 41,0 |
| E-Ready | No |
| Assembly Item no. Rim | • 39122972 |
| Load capacity of rim 1 [kg] | 8000 |
| Speed Rims 1 [km/h] | 40 |
| Load capacity of rim 2 [kg] | 7040 |
| Speed Rims 2 [km/h] | 65 |
| Maximum speed [km/h]. | 40 |
| Maximum air pressure [bar]. | 2,30 |
| Type of drive | Angetriebene & gezogene Achse |
| Hump | kein Hump |
| Single / multi-part | einteilig |
| Rim material | steel |
| RAL | RAL9006 |
| Cavity Sealed | No |
| Ventilation holes | No |
| Verschweißung beidseitig | No |
| Rim centering | BC |
| Number of bolt holes | 10 |
| Bolt hole design EUWA | B22 ES 36 |
| Bolt hole diameter [mm] | 27 |
| Countersinking | Sphere |
| Spherical countersink [mm]. | R18 |
| hub hole diameter [mm]. | 281 |
| Bolt hole circle diameter [mm] | 335 |
| Valve seat | External Valve |
| Valve hole diameter [mm] | 15.7 |

| |
|--------------------|
| Preassembled valve |
|--------------------|

| |
|----|
| No |
|----|
