

WHEELS

Product group	Wheels
Item number	59916254
Valid wheel size	650 / 85 R 38
Brand	Alliance
Tread pattern	Agri Star II
Valid rim size	DW 20 B x 38
Rim connection	10/281/335
Bolt hole design	B3
Offset (mm)	+50
Rim colour	Silver
Load capacity complete wheel [kg]	6500
Speed complete wheel [km/h]	65



Technical Informations

Assembly Item no. Tyres	• 15228805
LI / SI / PR	173 D
Load capacity 1 [kg]	6500
Speed 1 [km/h].	65
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	450,05
ECE regulation number	ECE 106
Section width (mm)	680
Stat. radius (SLR) [mm]	942
Rolling circumference [mm].	6201

Tread depth (mm)	61,0
Number of lugs	21x2
Tyre capacity 75% [ltr.]	933.23
E-Ready	No
Assembly Item no. Rim	• 39123043
Load capacity of rim 1 [kg]	8771
Speed Rims 1 [km/h]	65
Maximum speed [km/h].	65
Maximum air pressure [bar].	2,40
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Colour type	Glossy
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	10
Bolt hole design EUWA	B22 DS 36
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Valve seat	External Valve

Valve hole diameter [mm]	15.7
Preassembled valve	No
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade