

## WHEELS

Product group	Wheels
Item number	59916255
Valid wheel size	620 / 70 R 42
Brand	Alliance
Tread pattern	360
Valid rim size	DW 20 B x 42
Rim connection	10/281/335
Bolt hole design	B3
Offset (mm)	+6
Rim colour	Red
Load capacity complete wheel [kg]	6500
Speed complete wheel [km/h]	40
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



## Technical Informations

Assembly Item no. Tyres	• 15226831
LI / SI / PR	173 A8 / 170 B
Load capacity 1 [kg]	6500
Speed 1 [km/h].	40
Load capacity 2 [kg]	6000
Speed 2 [km/h].	50
Direction	Right
Antistatic	No
Tyre colour	Black

Nettogewicht [kg] (gültig)	438,95
ECE regulation number	ECE 106
Section width (mm)	650
Stat. radius (SLR) [mm]	887
Rolling circumference [mm].	5795
Tread depth (mm)	52,0
Number of lugs	24x2
E-Ready	No
Assembly Item no. Rim	• 39123096
Load capacity of rim 1 [kg]	8866
Speed Rims 1 [km/h]	65
Maximum speed [km/h].	50
Maximum air pressure [bar].	2,70
Number of bolt holes	10
Bolt hole design EUWA	B22 DS 36
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Single / multi-part	einteilig
Rim centering	BC
Rim material	steel
RAL	RAL3000
Cavity Sealed	No

---

Ventilation holes	No
Verschweißung beidseitig	No
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade