

WHEELS

Product group	Wheels
Item number	59916258
Valid wheel size	480 / 80 R 42
Brand	Alliance
Tread pattern	Agri Star II
Valid rim size	DW 16 L x 42
Rim connection	10/281/335
Bolt hole design	B3
Offset (mm)	+50
Rim colour	Silver
Load capacity complete wheel [kg]	3450
Speed complete wheel [km/h]	65



Technical Informations

Assembly Item no. Tyres	• 15228791
LI / SI / PR	151 D
Load capacity 1 [kg]	3450
Speed 1 [km/h].	65
Carcass properties	Stubble Guard
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	333,65
ECE regulation number	ECE 106
Section width (mm)	494
Stat. radius (SLR) [mm]	843

Rolling circumference [mm].	5429
Tread depth (mm)	54,0
Number of lugs	22x2
Tyre capacity 75% [ltr.]	423.23
E-Ready	No
Assembly Item no. Rim	• 39123098
Load capacity of rim 1 [kg]	5990
Maximum speed [km/h].	65
Maximum air pressure [bar].	1,60
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel
Surface treatment	SB
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	10
Bolt hole design EUWA	B22 DS 36
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Valve seat	External Valve

Valve hole diameter [mm]	15.7
Preassembled valve	No
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade