

## WHEELS

Product group	Wheels
Item number	59916261
Valid wheel size	480 / 80 R 46
Brand	Alliance
Tread pattern	Agri Star II
Valid rim size	DW 16 L x 46
Rim connection	10/281/335
Bolt hole design	B3
Offset (mm)	+50
Rim colour	Silver
Load capacity complete wheel [kg]	4250
Speed complete wheel [km/h]	50



## Technical Informations

Assembly Item no. Tyres	• 15228796
LI / SI / PR	158 D
Load capacity 1 [kg]	4250
Speed 1 [km/h].	65
Carcass properties	Stubble Guard
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	360,45
ECE regulation number	ECE 106
Section width (mm)	494
Stat. radius (SLR) [mm]	909

Rolling circumference [mm].	5873
Tread depth (mm)	54,0
Number of lugs	25x2
Tyre capacity 75% [ltr.]	457.65
E-Ready	No
Assembly Item no. Rim	• 39123004
Load capacity of rim 1 [kg]	6500
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	5980
Speed Rims 2 [km/h]	50
Maximum speed [km/h].	50
Maximum air pressure [bar].	2,40
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	10
Bolt hole design EUWA	B22 DS 36
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
hub hole diameter [mm].	281

---

<b>Bolt hole circle diameter [mm]</b>	335
<b>Valve seat</b>	External Valve
<b>Valve hole diameter [mm]</b>	15.7
<b>Preassembled valve</b>	No
<b>Valve design</b>	Metal valve
<b>Valve designation ETRTO</b>	V5.01.1
<b>Valve length [mm]</b>	50.0
<b>Valve angle [°]</b>	gerade