

## WHEELS

Product group	Wheels
Item number	59916264
Valid wheel size	VF 480 / 80 R 50
Brand	Alliance
Tread pattern	Agriflex 354 +
Valid rim size	TW 15 L x 50
Rim connection	10/281/335
Bolt hole design	B3
Rim colour	Silver
Load capacity complete wheel [kg]	5900
Speed complete wheel [km/h]	40



Bohnenkamp  
■ ■ ● Moving Professionals

 **ALLIANCE**  
ENGINEERED TO KEEP YOU AHEAD

## Technical Informations

Assembly Item no. Tyres	• 15226683
LI / SI / PR	171 D
Load capacity 1 [kg]	6150
Speed 1 [km/h].	65
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	462,26
ECE regulation number	ECE 106
Section width (mm)	494
Stat. radius (SLR) [mm]	942

Rolling circumference [mm].	6127
Tread depth (mm)	52,0
Number of lugs	30x2
Tyre capacity 75% [ltr.]	494
E-Ready	No
Assembly Item no. Rim	• 32013710
Load capacity of rim 1 [kg]	5900
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	5700
Speed Rims 2 [km/h]	50
Maximum speed [km/h].	50
Maximum air pressure [bar].	2,40
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Valve protection	VS H
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	10
Bolt hole design EUWA	B22 DS 36
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18

---

hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
Valve design	Rubber valve
Valve length [mm]	55.0
Valve angle [°]	gerade