

WHEELS

Product group	Wheels
Item number	59916313
Valid wheel size	VF 480 / 95 R 50
Brand	Alliance
Tread pattern	Agriflex 354 +
Valid rim size	W 15 L x 50
Rim connection	12/350/400
Bolt hole design	B3
Rim colour	Silver
Load capacity complete wheel [kg]	4690
Speed complete wheel [km/h]	65



Bohnenkamp
■ ■ ● Moving Professionals

 **ALLIANCE**
ENGINEERED TO KEEP YOU AHEAD

Technical Informations

Assembly Item no. Tyres	• 15226682
LI / SI / PR	176 D
Load capacity 1 [kg]	7100
Speed 1 [km/h].	65
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	438,33
ECE regulation number	ECE 106
Section width (mm)	485
Stat. radius (SLR) [mm]	984

Speed Radius Index (SRI)	1075
Rolling circumference [mm].	6537
Tread depth (mm)	53,0
Number of lugs	32x2
Tyre capacity 75% [ltr.]	585.75
E-Ready	No
Assembly Item no. Rim	• 39123165
Load capacity of rim 1 [kg]	4690
Speed Rims 1 [km/h]	65
Maximum speed [km/h].	65
Maximum air pressure [bar].	2,40
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Valve protection	VS H
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	12
Bolt hole design EUWA	B22 DS 36
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
hub hole diameter [mm].	350

Bolt hole circle diameter [mm]	400
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade