

WHEELS

Product group	Wheels
Item number	59916319
Valid wheel size	13.6 R 48
Brand	Alliance
Tread pattern	350
Valid rim size	W 12 x 48
Rim connection	10/281/335
Bolt hole design	B3
Offset (mm)	+50
Rim colour	Silver
Load capacity complete wheel [kg]	4375
Speed complete wheel [km/h]	40



Technical Informations

Assembly Item no. Tyres	• 15226396
LI / SI / PR	159 A8 / 156 D
Load capacity 1 [kg]	4375
Speed 1 [km/h].	40
Load capacity 2 [kg]	4000
Speed 2 [km/h].	65
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	300,94
ECE regulation number	ECE 106

Section width (mm)	345
Stat. radius (SLR) [mm]	854
Rolling circumference [mm].	5600
Tread depth (mm)	39,5
Tyre capacity 75% [ltr.]	251.25
E-Ready	No
Assembly Item no. Rim	• 39123170
Load capacity of rim 1 [kg]	4620
Speed Rims 1 [km/h]	65
Maximum speed [km/h].	65
Maximum air pressure [bar].	4,80
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Valve protection	VS H
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	10
Bolt hole design EUWA	B22 DS 36
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
hub hole diameter [mm].	281

Bolt hole circle diameter [mm]	335
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade