

WHEELS

Product group	Wheels
Item number	59916322
Valid wheel size	300 / 95 R 52
Brand	Alliance
Tread pattern	350
Valid rim size	W 10 x 52
Rim connection	10/281/335
Bolt hole design	B3
Offset (mm)	+100
Rim colour	Silver
Load capacity complete wheel [kg]	3960
Speed complete wheel [km/h]	65



Technical Informations

Assembly Item no. Tyres	• 15226685
LI / SI / PR	159 A8 / 156 D
Load capacity 1 [kg]	4375
Speed 1 [km/h].	40
Load capacity 2 [kg]	4000
Speed 2 [km/h].	65
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	326,02
ECE regulation number	ECE 106
Section width (mm)	310

Stat. radius (SLR) [mm]	887
Speed Radius Index (SRI)	925
Rolling circumference [mm].	5781
Tread depth (mm)	38,0
Tyre capacity 75% [ltr.]	213
E-Ready	No
Assembly Item no. Rim	• 39122997
Load capacity of rim 1 [kg]	3960
Speed Rims 1 [km/h]	65
Maximum speed [km/h].	65
Maximum air pressure [bar].	4,80
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Valve protection	VS H
Single / multi-part	einteilig
Rim material	steel
Surface treatment	SB
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	10
Bolt hole design EUWA	B22 DS 36
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18

hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade