

## WHEELS

Product group	Wheels
Item number	59916334
Valid wheel size	VF 445 / 50 R 22.5
Brand	Alliance
Tread pattern	Agriflex 381 +
Valid rim size	AG 14.00 x 22.5
Rim connection	10/281/335
Bolt hole design	A3
Rim colour	Silver
Load capacity complete wheel [kg]	4750
Speed complete wheel [km/h]	65



## Technical Informations

Assembly Item no. Tyres	• 15216106
LI / SI / PR	167 D
Load capacity 1 [kg]	5450
Speed 1 [km/h].	65
Carcass properties	All-Steel
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	129.15
ECE regulation number	ECE 106
Section width (mm)	437
Stat. radius (SLR) [mm]	454

Rolling circumference [mm].	3105
Tread depth (mm)	15,0
Tyre capacity 75% [litr.]	125.25
E-Ready	No
Assembly Item no. Rim	• 30840320
Load capacity of rim 1 [kg]	5600
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	4500
Speed Rims 2 [km/h]	80
Maximum speed [km/h].	65
Maximum air pressure [bar].	6,70
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	10
Bolt hole design EUWA	B22 ES 36
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335

---

Valve seat	External Valve
Valve hole diameter [mm]	9.7
Preassembled valve	No
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade