

WHEELS

Product group	Wheels
Item number	59916335
Valid wheel size	380 / 105 R 50
Brand	Alliance
Tread pattern	350
Valid rim size	DW 12 x 50
Rim connection	10/281/335
Bolt hole design	B3
Offset (mm)	+35
Rim colour	Silver
Load capacity complete wheel [kg]	5900
Speed complete wheel [km/h]	40



Technical Informations

Assembly Item no. Tyres	• 15226677
LI / SI / PR	171 A8 / 168 D
Load capacity 1 [kg]	6150
Speed 1 [km/h].	40
Load capacity 2 [kg]	5600
Speed 2 [km/h].	65
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	407,01
ECE regulation number	ECE 106
Section width (mm)	405

Stat. radius (SLR) [mm]	955
Rolling circumference [mm].	6214
Tread depth (mm)	39,0
Number of lugs	33x2
Tyre capacity 75% [ltr.]	490
E-Ready	No
Assembly Item no. Rim	• 32013703
Load capacity of rim 1 [kg]	5900
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	5700
Speed Rims 2 [km/h]	50
Maximum speed [km/h].	50
Maximum air pressure [bar].	4,40
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Valve protection	VS H
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Knurling	without knurling
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	10
Bolt hole design EUWA	B22 DS 36
Bolt hole diameter [mm]	27

Countersinking	Sphere
Spherical countersink [mm].	R18
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade