

## WHEELS

|                                   |                  |
|-----------------------------------|------------------|
| Product group                     | Wheels           |
| Item number                       | 59916336         |
| Valid wheel size                  | VF 520 / 85 R 46 |
| Brand                             | Alliance         |
| Tread pattern                     | Agriflex 354 +   |
| Valid rim size                    | DW 16 L x 46     |
| Rim connection                    | 12/350/400       |
| Bolt hole design                  | B3               |
| Rim colour                        | Silver           |
| Load capacity complete wheel [kg] | 5940             |
| Speed complete wheel [km/h]       | 65               |



Bohnenkamp  
■ ■ ● Moving Professionals

 **ALLIANCE**  
ENGINEERED TO KEEP YOU AHEAD

## Technical Informations

|                            |              |
|----------------------------|--------------|
| Assembly Item no. Tyres    | • 15226328   |
| LI / SI / PR               | 170 D        |
| Load capacity 1 [kg]       | 6000         |
| Speed 1 [km/h].            | 65           |
| Carcass properties         | Steel Belted |
| Antistatic                 | No           |
| Tyre colour                | Black        |
| Nettogewicht [kg] (gültig) | 417,65       |
| ECE regulation number      | ECE 106      |
| Section width (mm)         | 535          |
| Stat. radius (SLR) [mm]    | 906          |

|                             |                               |
|-----------------------------|-------------------------------|
| Speed Radius Index (SRI)    | 975                           |
| Rolling circumference [mm]. | 6050                          |
| Tread depth (mm)            | 53,0                          |
| Number of lugs              | 29x2                          |
| Tyre capacity 75% [ltr.]    | 606                           |
| E-Ready                     | No                            |
| Assembly Item no. Rim       | • 39123167                    |
| Load capacity of rim 1 [kg] | 5940                          |
| Speed Rims 1 [km/h]         | 65                            |
| Maximum speed [km/h].       | 65                            |
| Maximum air pressure [bar]. | 1,60                          |
| Type of drive               | Angetriebene & gezogene Achse |
| Hump                        | kein Hump                     |
| Valve protection            | VS H                          |
| Single / multi-part         | einteilig                     |
| Rim material                | steel                         |
| RAL                         | RAL9006                       |
| Cavity Sealed               | No                            |
| Ventilation holes           | No                            |
| Verschweißung beidseitig    | No                            |
| Rim centering               | BC                            |
| Number of bolt holes        | 12                            |
| Bolt hole design EUWA       | B22 DS 36                     |
| Bolt hole diameter [mm]     | 27                            |
| Countersinking              | Sphere                        |
| Spherical countersink [mm]. | R18                           |
| hub hole diameter [mm].     | 350                           |

---

|                                       |                |
|---------------------------------------|----------------|
| <b>Bolt hole circle diameter [mm]</b> | 400            |
| <b>Valve seat</b>                     | External Valve |
| <b>Valve hole diameter [mm]</b>       | 15.7           |
| <b>Preassembled valve</b>             | No             |
| <b>Valve design</b>                   | Metal valve    |
| <b>Valve designation ETRTO</b>        | V5.01.1        |
| <b>Valve length [mm]</b>              | 50.0           |
| <b>Valve angle [°]</b>                | gerade         |