

WHEELS

Product group	Wheels
Item number	59917316
Valid wheel size	500 / 45 - 22.5
Brand	BKT
Tread pattern	Flotation 558
Valid rim size	AG 16.00 x 22.5 H2
Rim connection	6/161/205
Bolt hole design	A2
Offset (mm)	-50
Rim colour	Silver
Rim series	Profiline
Load capacity complete wheel [kg]	3750
Speed complete wheel [km/h]	40
Nettogewicht [kg] (gültig)	110,53
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



Technical Informations

Assembly Item no. Tyres	• 15712515
LI / SI / PR	142 A8 / 154 A8, 16 PR
Load capacity 1 [kg]	2650
Speed 1 [km/h].	40
Load capacity 2 [kg]	3750
Speed 2 [km/h].	40
Maximum air pressure [bar].	3,60

TL/TT	TL
Tyre colour	Black
E-Ready	No
Antistatic	No
ECE regulation number	ECE 106
Section width (mm)	500
Stat. radius (SLR) [mm]	471
Rolling circumference [mm].	3167
Tread depth (mm)	19,0
Number of lugs	26x2
Assembly Item no. Rim	• 31612651
Load capacity of rim 1 [kg]	4375
Speed Rims 1 [km/h]	40
Maximum speed [km/h].	50
Type of drive	Angetriebene & gezogene Achse
Number of bolt holes	6
hub hole diameter [mm].	161
Bolt hole circle diameter [mm]	205
Bolt hole diameter [mm]	21.5
Bolt hole design EUWA	B18 ES 32
Countersinking	Sphere
Spherical countersink [mm].	R16
Rim centering	BC
Rim material	steel
RAL	RAL9006
Valve seat	External Valve
Ventilation holes	No

Single / multi-part	einteilig
Hump	H2
Cavity Sealed	No
Verschweißung beidseitig	No
Assembly Item no. Valve	• 47201039
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve hole diameter [mm]	15.7
Valve design	Rubber valve
Valve length [mm]	55.0
Valve angle [°]	gerade