

WHEELS

Product group	Wheels
Item number	59917317
Valid wheel size	500 / 45 - 22.5
Brand	BKT
Tread pattern	Flotation 558
Valid rim size	AG 16.00 x 22.5 H2
Rim connection	8/221/275
Bolt hole design	B2
Offset (mm)	-50
Rim colour	Silver
Load capacity complete wheel [kg]	3750
Speed complete wheel [km/h]	40
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



Bohnenkamp
■ ■ ● Moving Professionals

BKT
GROWING TOGETHER

Technical Informations

Assembly Item no. Tyres	• 15712515
LI / SI / PR	142 A8 / 154 A8, 16 PR
Load capacity 1 [kg]	2650
Speed 1 [km/h].	40
Load capacity 2 [kg]	3750
Speed 2 [km/h].	40
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	113,57

ECE regulation number	ECE 106
Section width (mm)	500
Stat. radius (SLR) [mm]	471
Rolling circumference [mm].	3167
Tread depth (mm)	19,0
Number of lugs	26x2
E-Ready	No
Assembly Item no. Rim	• 33060353
Load capacity of rim 1 [kg]	6800
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	5000
Speed Rims 2 [km/h]	65
Maximum speed [km/h].	40
Maximum air pressure [bar].	3,60
Number of bolt holes	8
hub hole diameter [mm].	221
Bolt hole circle diameter [mm]	275
Bolt hole diameter [mm]	21.5
Countersinking	Sphere
Spherical countersink [mm].	R16
Type of drive	Angetriebene & gezogene Achse
Hump	H2
Valve protection	VSH
Single / multi-part	einteilig
Rim centering	BC
Rim material	steel
RAL	RAL9006

Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade