

## WHEELS

Product group	Wheels
Item number	59917351
Valid wheel size	500 / 60 - 22.5
Brand	BKT
Tread pattern	Flotation V-Line
Valid rim size	AG 16.00 x 22.5 H2
Rim connection	6/161/205
Bolt hole design	A2
Offset (mm)	-50
Rim colour	Silver
Rim series	Profiline
Load capacity complete wheel [kg]	4375
Speed complete wheel [km/h]	40



## Technical Informations

Assembly Item no. Tyres	• 15712526
LI / SI / PR	151 A8 / 163 A8, 16 PR
Load capacity 1 [kg]	3450
Speed 1 [km/h].	40
Load capacity 2 [kg]	4875
Speed 2 [km/h].	40
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	127,24
ECE regulation number	ECE 106

Section width (mm)	500
Stat. radius (SLR) [mm]	510
Rolling circumference [mm].	3489
Tread depth (mm)	26,0
Number of lugs	28x2
E-Ready	No
Assembly Item no. Rim	• 31612651
Load capacity of rim 1 [kg]	4375
Speed Rims 1 [km/h]	40
Maximum speed [km/h].	40
Maximum air pressure [bar].	3,20
Type of drive	Angetriebene & gezogene Achse
Hump	H2
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	6
Bolt hole diameter [mm]	21.5
Countersinking	Sphere
Spherical countersink [mm].	R16
hub hole diameter [mm].	161
Bolt hole circle diameter [mm]	205
Valve seat	External Valve

---

Valve hole diameter [mm]	15.7
Preassembled valve	No
Valve design	Rubber valve
Valve length [mm]	55.0
Valve angle [°]	gerade