

WHEELS

Product group	Wheels
Item number	59917419
Valid wheel size	600 / 50 R 22.5
Brand	BKT
Tread pattern	FL 630 Ultra
Valid rim size	AG 20.00 x 22.5 TH2
Rim connection	8/221/275
Bolt hole design	A3
Rim colour	Silver
Rim series	Profiline
Load capacity complete wheel [kg]	6000
Speed complete wheel [km/h]	40
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



Technical Informations

Assembly Item no. Tyres	• 15715142
LI / SI / PR	170 A8 / 159 D
Load capacity 1 [kg]	6000
Speed 1 [km/h].	40
Load capacity 2 [kg]	4375
Speed 2 [km/h].	65
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	172,15

ECE regulation number	ECE 106
Section width (mm)	611
Stat. radius (SLR) [mm]	518
Speed Radius Index (SRI)	550
Rolling circumference [mm].	3533
Tread depth (mm)	30,5
E-Ready	No
Assembly Item no. Rim	• 32012688
Load capacity of rim 1 [kg]	7070
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	5310
Speed Rims 2 [km/h]	65
Maximum speed [km/h].	65
Maximum air pressure [bar].	4,00
Number of bolt holes	8
Bolt hole design EUWA	B22 ES 36
hub hole diameter [mm].	221
Bolt hole circle diameter [mm]	275
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
Type of drive	Angetriebene & gezogene Achse
Hump	TH2
Single / multi-part	einteilig
Rim centering	BC
Rim material	steel
RAL	RAL9006

Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade