

WHEELS

Product group	Wheels
Item number	59917435
Valid wheel size	600 / 60 R 28
Brand	Alliance
Tread pattern	Forestar 342
Valid rim size	DW 18 x 28
Rim connection	10/281/335
Offset (mm)	-90
Rim colour	Silver
Load capacity complete wheel [kg]	4375
Speed complete wheel [km/h]	40





Technical Informations

Assembly Item no. Tyres	15226749
LI / SI / PR	167 A2 / 159 A8
Load capacity 1 [kg]	5450
Speed 1 [km/h].	10
Load capacity 2 [kg]	4375
Speed 2 [km/h].	40
TRA Code	LS-2
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	309,01
ECE regulation number	ECE 106

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Section width (mm)	616
Stat. radius (SLR) [mm]	660
Rolling circumference [mm].	4335
Tread depth (mm)	50,0
Number of lugs	18x2
Tyre capacity 75% [ltr.]	331.5
E-Ready	No
Assembly Item no. Rim •	32100755
Load capacity of rim 1 [kg]	4500
Speed Rims 1 [km/h]	40
Maximum speed [km/h].	40
Maximum air pressure [bar].	3,20
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Valve protection	VS V
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Forest reinforcement	flange reinforcement Ø19 mm
Knurling	without knurling
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	НВ
Number of bolt holes	10
Bolt hole design EUWA	M20
Bolt hole diameter [mm]	24

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No