

## WHEELS

|                                   |                     |
|-----------------------------------|---------------------|
| Product group                     | Wheels              |
| Item number                       | 59917483            |
| Valid wheel size                  | 710 / 40 - 22.5     |
| Brand                             | BKT                 |
| Tread pattern                     | TR 678              |
| Valid rim size                    | AG 24.00 x 22.5 TH2 |
| Rim connection                    | 10/281/335          |
| Bolt hole design                  | A3                  |
| Offset (mm)                       | -50                 |
| Rim colour                        | Silver              |
| Rim series                        | Profiline           |
| Load capacity complete wheel [kg] | 6500                |
| Speed complete wheel [km/h]       | 40                  |
| RDRA (Reifendruckregelanlage)     | No                  |
| RDKS (Reifendruckkontrollsystem)  | No                  |



## Technical Informations

|                         |                 |
|-------------------------|-----------------|
| Assembly Item no. Tyres | • 15712608      |
| LI / SI / PR            | 173 A8          |
| Load capacity 1 [kg]    | 6500            |
| Speed 1 [km/h].         | 40              |
| TRA Code                | LS-2            |
| Carcass properties      | HD Steel Belted |
| Antistatic              | No              |
| Tyre colour             | Black           |

|                                |                               |
|--------------------------------|-------------------------------|
| Nettogewicht [kg] (gültig)     | 235,90                        |
| ECE regulation number          | ECE 106                       |
| Section width (mm)             | 707                           |
| Stat. radius (SLR) [mm]        | 545                           |
| Rolling circumference [mm].    | 3624                          |
| Tread depth (mm)               | 37,5                          |
| Number of lugs                 | 17x2                          |
| E-Ready                        | No                            |
| Assembly Item no. Rim          | • 32012784                    |
| Load capacity of rim 1 [kg]    | 8040                          |
| Speed Rims 1 [km/h]            | 40                            |
| Load capacity of rim 2 [kg]    | 6640                          |
| Speed Rims 2 [km/h]            | 65                            |
| Maximum speed [km/h].          | 40                            |
| Maximum air pressure [bar].    | 6,00                          |
| Number of bolt holes           | 10                            |
| Bolt hole design EUWA          | B22 ES 36                     |
| hub hole diameter [mm].        | 281                           |
| Bolt hole circle diameter [mm] | 335                           |
| Bolt hole diameter [mm]        | 27                            |
| Countersinking                 | Sphere                        |
| Spherical countersink [mm].    | R18                           |
| Type of drive                  | Angetriebene & gezogene Achse |
| Hump                           | TH2                           |
| Single / multi-part            | einteilig                     |
| Rim centering                  | BC                            |
| Rim material                   | steel                         |

---

|                                 |                  |
|---------------------------------|------------------|
| <b>RAL</b>                      | RAL9006          |
| <b>Cavity Sealed</b>            | No               |
| <b>Knurling</b>                 | without knurling |
| <b>Ventilation holes</b>        | No               |
| <b>Verschweißung beidseitig</b> | No               |
| <b>Valve seat</b>               | External Valve   |
| <b>Valve hole diameter [mm]</b> | 15.7             |
| <b>Preassembled valve</b>       | No               |
| <b>TPMS-kompatibles Ventil</b>  | No               |
| <b>Valve design</b>             | Metal valve      |
| <b>Valve designation ETRTO</b>  | V5.01.1          |
| <b>Valve length [mm]</b>        | 50.0             |
| <b>Valve angle [°]</b>          | gerade           |