

## WHEELS

Product group	Wheels
Item number	59917591
Valid wheel size	650 / 55 R 26.5
Brand	BKT
Tread pattern	FL 630 Super
Valid rim size	AG 20.00 x 26.5 TH2
Rim connection	10/281/335
Bolt hole design	A3
Rim colour	Silver
Rim series	Profiline
Load capacity complete wheel [kg]	7500
Speed complete wheel [km/h]	65
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



## Technical Informations

Assembly Item no. Tyres	• 15715214
LI / SI / PR	178 D
Load capacity 1 [kg]	7500
Speed 1 [km/h].	65
Carcass properties	HD Steel Belted
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	242,12
ECE regulation number	ECE 106

Section width (mm)	645
Stat. radius (SLR) [mm]	628
Rolling circumference [mm].	4292
Tread depth (mm)	24,5
E-Ready	No
Assembly Item no. Rim	• 32012882
Load capacity of rim 1 [kg]	10200
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	7500
Speed Rims 2 [km/h]	65
Maximum speed [km/h].	65
Maximum air pressure [bar].	6,00
Number of bolt holes	10
Bolt hole design EUWA	B22 ES 36
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
Type of drive	Angetriebene & gezogene Achse
Hump	TH2
Single / multi-part	einteilig
Rim centering	BC
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Knurling	without knurling

---

Ventilation holes	No
Verschweißung beidseitig	No
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade