

WHEELS

Product group	Wheels
Item number	59917600
Valid wheel size	500 / 55 - 20
Brand	Alliance
Tread pattern	FarmPRO 327
Valid rim size	16 x 20
Rim connection	10/281/335
Bolt hole design	A3
Rim colour	Silver
Load capacity complete wheel [kg]	2360
Speed complete wheel [km/h]	40
Nettogewicht [kg] (gültig)	106,07
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



Technical Informations

Assembly Item no. Tyres	• 15212568
LI / SI / PR	138 A8 / 150 A8, 10 PR
Load capacity 1 [kg]	2360
Speed 1 [km/h].	40
Load capacity 2 [kg]	3350
Speed 2 [km/h].	40
Maximum air pressure [bar].	2,40
TL/TT	TL
Tyre colour	Black

E-Ready	No
Antistatic	No
ECE regulation number	ECE 106
Section width (mm)	503
Stat. radius (SLR) [mm]	464
Rolling circumference [mm].	3063
Tread depth (mm)	12,6
Assembly Item no. Rim	• 31610601
Load capacity of rim 1 [kg]	5000
Speed Rims 1 [km/h]	40
Maximum speed [km/h].	40
Type of drive	Towed axle
Number of bolt holes	10
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Bolt hole diameter [mm]	27
Bolt hole design EUWA	B22 ES 36
Countersinking	Sphere
Spherical countersink [mm].	R18
Rim centering	BC
Rim material	steel
RAL	RAL9006
Valve seat	External Valve
Ventilation holes	No
Single / multi-part	einteilig
Hump	kein Hump
Cavity Sealed	No

Verschweißung beidseitig	No
Assembly Item no. Valve	• 47201039
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve hole diameter [mm]	15.7
Valve design	Rubber valve
Valve length [mm]	55.0
Valve angle [°]	gerade