

WHEELS

Product group	Wheels
Item number	59917606
Valid wheel size	500 / 55 - 20
Brand	Alliance
Tread pattern	FarmPRO 327
Valid rim size	16 x 20
Rim connection	6/161/205
Bolt hole design	A2
Offset (mm)	-55
Rim colour	Silver
Load capacity complete wheel [kg]	3350
Speed complete wheel [km/h]	40



Technical Informations

Assembly Item no. Tyres	• 15212568
LI / SI / PR	138 A8 / 150 A8, 10 PR
Load capacity 1 [kg]	2360
Speed 1 [km/h].	40
Load capacity 2 [kg]	3350
Speed 2 [km/h].	40
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	106,21
ECE regulation number	ECE 106
Section width (mm)	503

Stat. radius (SLR) [mm]	464
Rolling circumference [mm].	3063
Tread depth (mm)	12,6
E-Ready	No
Assembly Item no. Rim	• 31610620
Load capacity of rim 1 [kg]	3625
Speed Rims 1 [km/h]	40
Maximum speed [km/h].	50
Maximum air pressure [bar].	2,40
Type of drive	Towed axle
Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	6
Bolt hole diameter [mm]	21.5
Countersinking	Sphere
Spherical countersink [mm].	R16
hub hole diameter [mm].	161
Bolt hole circle diameter [mm]	205
Valve seat	External Valve
Preassembled valve	No
Valve design	Metal valve

Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade