

WHEELS

Product group	Wheels
Item number	59917621
Valid wheel size	800 / 45 R 26.5
Brand	BKT
Tread pattern	FL 630 Ultra
Valid rim size	AG 28.00 x 26.5 TH2
Rim connection	10/281/335
Bolt hole design	A3
Offset (mm)	-50
Rim colour	Silver
Rim series	Profiline
Load capacity complete wheel [kg]	9000
Speed complete wheel [km/h]	40
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



Technical Informations

Assembly Item no. Tyres	• 15715231
LI / SI / PR	184 A8 / 174 D
Load capacity 1 [kg]	9000
Speed 1 [km/h].	40
Load capacity 2 [kg]	6700
Speed 2 [km/h].	65
Antistatic	No
Tyre colour	Black

Nettogewicht [kg] (gültig)	311,45
ECE regulation number	ECE 106
Section width (mm)	828
Stat. radius (SLR) [mm]	618
Speed Radius Index (SRI)	675
Rolling circumference [mm].	4238
Tread depth (mm)	31,5
E-Ready	No
Assembly Item no. Rim	• 32013031
Load capacity of rim 1 [kg]	9930
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	7300
Speed Rims 2 [km/h]	65
Maximum speed [km/h].	65
Maximum air pressure [bar].	4,00
Number of bolt holes	10
Bolt hole design EUWA	B22 ES 36
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
Type of drive	Angetriebene & gezogene Achse
Hump	TH2
Single / multi-part	einteilig
Rim centering	BC
Rim material	steel

RAL	RAL9006
Cavity Sealed	No
Knurling	without knurling
Ventilation holes	No
Verschweißung beidseitig	No
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade