

## WHEELS

Product group	Wheels
Item number	59917631
Valid wheel size	500 / 55 R 20
Brand	Alliance
Tread pattern	Lawn Master 221
Valid rim size	16 x 20
Rim connection	6/161/205
Bolt hole design	A2
Rim colour	Silver
Load capacity complete wheel [kg]	4500
Speed complete wheel [km/h]	50



## Technical Informations

Assembly Item no. Tyres	• 15215077
LI / SI / PR	160 B
Load capacity 1 [kg]	4500
Speed 1 [km/h].	50
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	113,01
ECE regulation number	ECE 106
Section width (mm)	505
Stat. radius (SLR) [mm]	455
Rolling circumference [mm].	3250

Tread depth (mm)	22,0
Number of lugs	10x2
E-Ready	No
Assembly Item no. Rim	• 31610602
Load capacity of rim 1 [kg]	4750
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	4500
Speed Rims 2 [km/h]	50
Maximum speed [km/h].	50
Maximum air pressure [bar].	4,20
Type of drive	Towed axle
Hump	kein Hump
Valve protection	VS H
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	6
Bolt hole diameter [mm]	21.5
Countersinking	Sphere
Spherical countersink [mm].	R16
hub hole diameter [mm].	161
Bolt hole circle diameter [mm]	205
Valve seat	External Valve

---

Preassembled valve	No
Valve design	Rubber valve
Valve length [mm]	55.0
Valve angle [°]	gerade